

Technical data

General features of the series

DP1.2-VISION-CAT SERIES		
Interfaces for computers	Video:	▸ see specific features
	PS/2 keyboard:	1 × PS/2 socket
	USB keyboard/mouse:	1 × USB-B socket
	Audio:	3.5-mm jack plug (Line In) 3.5-mm jack plug (Line Out)
	USB 2.0:	▸ Variant -ARU Shared transmission of signals of USB devices as well as keyboard and mouse via USB-B socket.
		▸ Variant -ARU2 1 × USB-B socket
RS232:	1 × RS232 socket	
Interfaces for remote console	Monitor:	▸ see specific features
	PS/2 keyboard/mouse:	1 × PS/2 socket
	USB keyboard/mouse:	2 × USB-A socket
	Generic-HID:	1 × USB-A socket
	Audio:	3.5-mm jack plug (Speaker) 3.5-mm jack plug (Line In)
	USB 2.0:	2 × USB-A socket
	▸ Variant -ARU	
	USB 2.0:	4 × USB-A socket
▸ Variant -ARU2		
RS232:	1 × RS232 plug	
Interfaces for local console	Monitor:	▸ see specific features
	PS/2 keyboard:	1 × PS/2 socket
	USB keyboard/mouse:	2 × USB-A socket
Other interfaces	Connection to network:	1 × RJ 45 socket (10/100 MBit/s)
	Service:	1 × Mini-USB socket (type B)
Audio ▸ DisplayPort Digital	Transmission type:	2 channel LPCM, stereo
	Resolutions:	16/20/24 bit
	Sampling rates:	up to 48 kHz
Audio	Transmission type:	transparent, bidirectional
	Resolution:	24 bit digital, Stereo
	Sampling rate:	96 kHz
	Bandwidth:	22 kHz

DP1.2-VISION-CAT SERIES		
Graphics	Format:	DisplayPort (DP 1.2a)
	Colour depth:	24 Bit
	Pixel encoding:	RGB 4:4:4 with24bpp/8bpc
	Videobandwidth:	max. 600 MP/s, DisplayPort 4 Lanes, LBR, HBR, HBR2, SingleStreamTransport (SST)
	Max. resolution per video channel:	<ul style="list-style-type: none"> ▪ 2560 × 1600 @ 60Hz ▪ 4096 × 2160 @ 60Hz (4Kp60Hz)
	Exemplary resolutions:	per video channel: <ul style="list-style-type: none"> ▪ 1920 × 1200 @ 60Hz ▪ 2048 × 2048 @ 60Hz (2K × 2K) ▪ 2560 × 1600 @ 60Hz ▪ 3840 × 2160 @ 60Hz (Ultra HD/60Hz) ▪ 4096 × 2160 @ 60Hz (4Kp60Hz) ▶ further standardised resolutions possible
	Vertical frequency:	24 Hz to 200 Hz
	Horizontal frequency:	25 kHz to 185 kHz
RS232	Transmission type:	transparent
	Transmission rate:	max. 115.200 bit/s
	Supported signals:	RxD, TxD, RTS, CTS, DTR, DSR, DCD
USB 2.0 full speed ▶ -ARU variant	Specification:	USB 2.0
	Transmission type:	transparent
	Supported devices:	high power devices (up to 500 mA)
	Range:	max. 140 meters
USB 2.0 high speed ▶ -ARU2 variant	Specification:	USB 2.0
	Transmission type:	transparent
	Transmission rate:	max. 480 Mbit/s
	Supported devices:	high power devices (up to 500 mA)
	Range:	max. 100 meters
Main power supply	Type:	internal power pack
	Connector:	IEC plug (IEC-320 C14)
	Voltage:	AC100-240V/60-50Hz
Redundant power supply	Type:	external power pack
	Connector:	miniDIN-4 Power socket
	Voltage:	+12VDC

Specific features of single-channel devices

DP1.2-VISION-CAT-CPU		
Interfaces for local console	Monitor:	1 × DisplayPort jack
Interfaces for computer	Video:	1 × DisplayPort jack
Interfaces to computer module	KVM, Audio and RS232: ‣ When using the -ARU variant the signals of USB 2.0 devices are transmitted via this cable.	1 × RJ 45 socket
	USB 2.0 ‣ -ARU2 variant	1 × RJ 45 socket
	Transmission 2: ‣ -UC variant	1 × RJ 45 socket
Casing	Material:	anodised aluminium
	Dimensions (W × H × D):	210 × 44 × 210 mm (Desktop) 19" × 1 U × 210 mm (Rackmount)
	Weight:	approx. 1.4 kg
Operating environment	Temperature:	+5 to +45 °C
	Air humidity:	< 80 %, non-condensing
DP1.2-VISION-CAT-CON		
Interfaces for remote console	Monitor:	1 × DisplayPort jack
Interface to computer module	KVM, Audio and RS232: ‣ When using the -ARU variant the signals of USB 2.0 devices are additionally transmitted via this cable.	1 × RJ 45 socket
	USB 2.0 ‣ -ARU2 variant	1 × RJ 45 socket
	Transmission 2: ‣ -CON-2 variant	1 × RJ 45 socket
Casing	Material:	anodised aluminium
	Dimensions (W × H × D):	210 × 44 × 210 mm (Desktop) 19" × 1 U × 210 mm (Rackmount)
	Weight:	approx. 1.4 kg
Operating environment	Temperature:	+5 to +45 °C
	Air humidity:	< 80 %, non-condensing

Specific features of multi-channel devices

DP1.2-VISION-CAT-MC2-CPU		
Interfaces for local console	Monitor:	2 × DisplayPort jack
Interfaces for computer	Video:	2 × DisplayPort jack
Interfaces to user module	KVM, Audio and RS232: ‣ When using the -ARU variant the signals of USB 2.0 devices are transmitted via this cable.	2 × RJ 45 socket
	USB 2.0 ‣ -ARU2 variant	1 × RJ 45 socket
Casing	Material:	anodised aluminium
	Dimensions (W × H × D):	270 × 44 × 210 mm
	Weight:	approx. 1.7 kg
Operating environment	Temperature:	+5 to +45 °C
	Air humidity:	< 80 %, non-condensing
DP1.2-VISION-CAT-MC2-CON		
Interfaces for remote console	Monitor:	2 × DisplayPort jack
Interface to computer module	KVM, Audio and RS232: ‣ When using the -ARU variant the signals of USB 2.0 devices are additionally transmitted via this cable.	2 × RJ 45 socket
	USB 2.0 ‣ -ARU2 variant	1 × RJ 45 socket
Casing	Material:	anodised aluminium
	Dimensions (W × H × D):	270 × 44 × 210 mm
	Weight:	approx. 1.7 kg
Operating environment	Temperature:	+5 to +45 °C
	Air humidity:	< 80 %, non-condensing

DP1.2-VISION-CAT-MC4-CPU

Interfaces for local console	Monitor:	4 × DisplayPort jack
	Interfaces to computer	Video:
Interfaces to user module	KVM, Audio and RS232: ‣ When using the -ARU variant the signals of USB 2.0 devices are transmitted via this cable.	4 × RJ 45 socket
	USB 2.0 ‣ -ARU2 variant	1 × RJ 45 socket
Casing	Material:	anodised aluminium
	Dimensions (W × H × D):	435 × 44 × 210 mm
	Weight:	approx. 2.5 kg
Operating environment	Temperature:	+5 to +45 °C
	Air humidity:	< 80 %, non-condensing

DP1.2-VISION-CAT-MC4-CON

Interfaces for remote console	Monitor:	4 × DisplayPort jack
	Interface to computer module	KVM, Audio and RS232: ‣ When using the -ARU variant the signals of USB 2.0 devices are additionally transmitted via this cable.
USB 2.0 ‣ -ARU2 variant		1 × RJ 45 socket
Casing	Materialien:	anodised aluminium
	Dimensions (W × H × D):	435 × 44 × 210 mm
	Weight:	approx. 2.5 kg
Operating environment	Temperature:	‣ -AR variant +5 to +45 °C
		‣ -ARU and -ARU2 variant +5 to +40 °C
	Air humidity:	< 80 %, non-condensing

English

Current consumption

Device variant	Main power supply	Redundant power supply
AR-CPU	100-240V/60-50Hz/0.5-0.3A	12VDC/1.9A
AR-CPU-UC	100-240V/60-50Hz/0.6-0.3A	12VDC/2.0A
AR-CON	100-240V/60-50Hz/0.5-0.2A	12VDC/1.9A
AR-CON-2	100-240V/60-50Hz/0.6-0.3A	12VDC/2.2A
ARU-CPU	100-240V/60-50Hz/0.5-0.3A	12VDC/1.9A
ARU-CPU-UC	100-240V/60-50Hz/0.6-0.3A	12VDC/2.0A
ARU-CON	100-240V/60-50Hz/0.7-0.3A	12VDC/2.9A
ARU-CON-2	100-240V/60-50Hz/0.8-0.5A	12VDC/3.2A
ARU2-CPU	100-240V/60-50Hz/0.5-0.3A	12VDC/2.0A
ARU2-CON	100-240V/60-50Hz/0.7-0.3A	12VDC/3.1A
MC2-AR-CPU	100-240V/60-50Hz/0.6-0.3A	12VDC/3.2A
MC2-AR-CON	100-240V/60-50Hz/0.7-0.3A	12VDC/4.2A
MC2-ARU-CPU	100-240V/60-50Hz/0.6-0.3A	12VDC/3.2A
MC2-ARU-CON	100-240V/60-50Hz/0.8-0.4A	12VDC/4.2A
MC2-ARU2-CPU	100-240V/60-50Hz/0.6-0.3A	12VDC/3.3A
MC2-ARU2-CON	100-240V/60-50Hz/0.8-0.4A	12VDC/4.4A
MC4-AR-CPU	100-240V/60-50Hz/0.8-0.4A	12VDC/5.7A
MC4-AR-CON	100-240V/60-50Hz/0.8-0.4A	12VDC/5.7A
MC4-ARU-CPU	100-240V/60-50Hz/0.8-0.4A	12VDC/5.7A
MC4-ARU-CON	100-240V/60-50Hz/1.0-0.5A	12VDC/6.7A
MC4-ARU2-CPU	100-240V/60-50Hz/0.8-0.4A	12VDC/5.8A
MC4-ARU2-CON	100-240V/60-50Hz/1.0-0.5A	12VDC/6.9A