

Technical data

General features of the series

DP1.2-MUX3-ATC SERIES		
Number of video sources	Per computer/workstation:	▸ See variant features
Workstation	Connectors per device:	1
	Connection:	Directly on the device
Interfaces for workstation	Video:	▸ See variant features
	PS/2 keyboard/mouse	1 × PS/2 socket ▸ Adapter for additional PS/2 interface available
	USB keyboard/mouse:	2 × USB A socket
	USB 3.0 devices:	2 × USB A socket
	Audio:	1 × 3.5 mm jack plug (speakers) 1 × Cinch (RCA) socket (Dig. Audio Out)
	External switch:	1 × RS232 socket
Computer	Connectors per device:	3
	Connection:	With optional cable sets on the device
Interfaces per computer	Video:	▸ See variant features
	PS/2:	1 × PS/2 socket ▸ Adapter for additional PS/2 interface available
	USB:	1 × USB B socket
	USB 3.0:	1 × USB B socket
	Audio:	1 × 3.5 mm jack plug (line in)
	Other interfaces	Network:
Service:		1 × Mini USB B socket
Audio ▸ DisplayPort digital ▸ Digital audio out	Transmission type:	Digital, unidirectional, embedded in DisplayPort signal
	Resolutions:	16/20/24 bit
	Sampling rates:	Up to 48 kHz
	Digital Audio Out:	De-embedding of embedded audio in DisplayPort signal
Audio ▸ Line In/Speaker	Type:	Analogue, transparent
	Resolution:	24 bit digital, stereo
	Sampling rate:	96 kHz
	Bandwidth	22 kHz

Technical data

Graphics	Signal input:	DisplayPort 1.2a (LBR, HBR, HBR2, SST, MST)
	Signal output:	DisplayPort 1.2a (LBR, HBR, HBR2, SST, MST)
	Colour depth:	24 bits
	Exemplary resolutions:	<ul style="list-style-type: none"> ▪ 4096 × 2160 @ 60 Hz (4K/60 Hz) ▪ 3840 × 2160 @ 60 Hz (Ultra HD/60 Hz) ▪ 2560 × 1600 @ 60 Hz ▪ 1920 × 1200 @ 60 Hz ▪ 2048 × 2048 @ 60 Hz (2K x 2K) <p>› Other standard resolutions within the max. pixel rate and refresh rates between 20 and 120 Hz possible.</p>
	Pixel rate:	25 MPixel/s to 600 MPixel/s
	Pixel coding:	RGB 4:4:4 with 24 bpp/8 bpc
	EDID incl. DDC/CI:	E-DID support via DP AUX channel
USB	Specification:	USB 3.1 Gen 1 (USB 3.0/USB 2.0 compatible)
	Transmission rate:	SuperSpeed 5.0 Gbps (low speed, full speed, hi speed compatible)
	Power (output):	HighPower (0.9A)
	Max. cable length:	<ul style="list-style-type: none"> ▪ USB 3.0/USB 3.1: max. 3 m ▪ USB 2.0: max. 5 m
Main power supply	Type:	Internal power pack
	Connection:	IEC plug (IEC-320 C14)
Redundant power supply	Type:	Internal power pack
	Connection:	IEC plug (IEC-320 C14)
Power consumption	Maximum:	› see variant features
Operating environment	Temperature:	+5°C to +45°C
	Air humidity:	< 80%, non-condensing
Conformity		CE, RoHS

Individual variant features

DP1.2-MUX3-ATC		
Number of video sources	Per computer/ workstation:	1
Interfaces for workstation	Video:	1 × DisplayPort socket
Interfaces per computer	Video:	1 × DisplayPort socket
Power supply	Power consumption:	0.4 A@240VAC; 0.9 mA@100VAC
Housing	Material:	Anodised aluminium
	Dimensions (W × H × D):	435 × 44 × 210 mm
	Weight:	Approx. 2.7 kg
DP1.2-MUX3-ATC-MC2		
Number of video sources	Per computer/ workstation:	2
Interfaces for workstation	Video:	2 × DisplayPort socket
Interfaces per computer	Video:	2 × DisplayPort socket
Power supply	Power consumption:	0.5 A@240VAC; 1.2 mA@100VAC
Housing	Material:	Anodised aluminium
	Dimensions (W × H × D):	435 × 88 × 210 mm
	Weight:	Approx. 3.5 kg