

# Technical data

OPERATORPANEL2		
<b>Channel switching</b>	Switchable channels:	2
	Interface to KVM switch:	1 × RS232
	Compatible KVM switches:	<ul style="list-style-type: none"> <li>▸ DL-MUX4</li> <li>▸ DVIMUX</li> <li>▸ DVIMUX8-OSD</li> <li>▸ TradeSwitch</li> </ul>
<b>Power supply</b>	Type:	External power pack
	Connector:	Mini-DIN 4 socket
	Power input:	12VDC/100mA
<b>Housing</b>	Material:	Anodised aluminium
	Dimensions (W × H × D):	<ul style="list-style-type: none"> <li>▸ 115 × 47 × 93 mm (Desktop)</li> <li>▸ 143 × 47 × 183 mm (Deskmount)</li> </ul>
	Weight:	Approx. 350 g
<b>Operational environment</b>	Temperature:	+5 to +45 °C
	Air humidity:	< 80%, non condensing
<b>Conformity</b>		CE, RoHS
OPERATORPANEL4		
<b>Power connectors for external devices</b>	Switchable channels:	4
	Interface to KVM switch:	1 × RS232
	Compatible KVM switches:	<ul style="list-style-type: none"> <li>▸ DL-MUX4</li> <li>▸ DVIMUX</li> <li>▸ DVIMUX8-OSD</li> <li>▸ TradeSwitch</li> </ul>
<b>Power supply</b>	Type:	External power pack
	Connector:	Mini-DIN 4 socket
	Power input:	12VDC/100mA
<b>Housing</b>	Material:	Anodised aluminium
	Dimensions (W × H × D):	<ul style="list-style-type: none"> <li>▸ 115 × 47 × 93 mm (Desktop)</li> <li>▸ 143 × 47 × 183 mm (Deskmount)</li> </ul>
	Weight:	Approx. 350 g
<b>Operational environment</b>	Temperature:	+5 to +45 °C
	Air humidity:	< 80%, non condensing
<b>Conformity</b>		CE, RoHS

Technical data

<b>OPERATORPANEL8</b>		
<b>Power connectors for external device</b>	Switchable channels:	8
	Interface to KVM switch:	1 × RS232
	Compatible KVM switches:	<ul style="list-style-type: none"> <li>▸ DL-MUX4</li> <li>▸ DVIMUX</li> <li>▸ DVIMUX8-OSD</li> <li>▸ TradeSwitch</li> </ul>
<b>Power supply</b>	Type:	External power pack
	Connector:	Mini-DIN 4 socket
	Power input:	12VDC/100mA
<b>Housing</b>	Material:	Anodised aluminium
	Dimensions (W × H × D):	<ul style="list-style-type: none"> <li>▸ 115 × 47 × 93 mm (Desktop)</li> <li>▸ 143 × 47 × 183 mm (Deskmount)</li> </ul>
	Weight:	Approx. 350 g
<b>Operational environment</b>	Temperature:	+5 to +45 °C
	Air humidity:	< 80%, non condensing
<b>Conformity</b>		CE, RoHS