

# Technical data

<b>G&amp;D RACKCONSOLE-PRO 17HR</b>		
<b>Signals</b>	Image sources:	DisplayPort, DVI-D, DVI-A (VGA), HDMI
	Keyboard/Mouse:	USB
<b>Display</b>	Height:	17"
	Technology:	TFT-LCD with LED backlight
	Resolution:	1920 × 1200 (WUXGA)
	Refresh rate:	60 Hz
	Pixel pitch:	0.1905 × 0.1905 mm
	Colours:	24 bit (16.7 mio.)
	Brightness:	600 cd/m <sup>2</sup>
	Contrast ratio:	typ. 2000:1
	Horizontal angle:	+ 88 °/- 88 ° (ultra wide viewing angle)
	Vertical angle:	+ 88 °/- 88 ° (ultra wide viewing angle)
	Backlight:	LED
	Response time:	20+9 ms
<b>Supported resolutions</b>	Max. Resolution:	2560 × 1600 @ 60 Hz (digital) 1920 × 1200 @ 60Hz (analog)
	Exemplary resolutions:	<ul style="list-style-type: none"><li>▪ 2560 × 1440 @ 60Hz</li><li>▪ 1920 × 1080 @ 60Hz (1080p)</li><li>▪ 1920 × 1080 @ 60Hz (1080i)</li></ul> <p>‣ Resolutions that deviate from the displays resolution are scaled to 1920 × 1200 pixels for output as best as possible.</p>
<b>Housing</b>	Dimensions:	483 × 44 × 628 mm (w × h × d)
	Weight:	Approx. 15 kg
	Cable routing:	Cable chain
<b>Permissible installation depth</b>	Min. installation depth:	570 mm
	Max. installation depth:	740 mm
<b>Stromversorgung</b>	Input voltage:	100-240 V AC, 60-50 Hz
<b>Power input</b>	100 VAC:	52 W
	240 VAC:	51 W
	12 VDC:	51 W
<b>Current consumption</b>	100-240 VAC:	1.1 A - 0.6 A
	12 VDC:	4.2 A
<b>Power input</b>	Operation:	Approx. 52 W
	Standby:	< 1 W

# Technical data

## G&D RACKCONSOLE-LED 17HR

<b>Signals</b>	Image sources:	DVI-I, DVI-A (VGA), DisplayPort
	Keyboard/Mouse:	PS/2 or USB (depending on type)
<b>Display</b>	Height:	17" wide screen
	Technology:	LCD-TFT active Matrix
	Resolution:	1920 × 1200 (WUXGA)
	Refresh rate:	60 Hz
	Pixel pitch:	0.191 × 0.191
	Colours:	24 bit (16.7 M)
	Brightness:	600 nits
	Contrast ratio:	2000:1
	Horizontal angle:	+ 88 °/- 88 ° (ultra wide viewing angle)
	Vertical angle:	+ 88 °/- 88 ° (ultra wide viewing angle)
	Backlight:	LED
	Response time:	typ. 29 ms
	<b>Casing</b>	Dimensions:
Installation depth:		560 - 850 mm (distance between 19" profiles)
Weight:		Approx. 12 kg
Cable routing:		Cable chain
<b>Power supply</b>	Supply voltage:	100-240 V AC, 50/60 Hz
<b>Power input</b>	Operation:	Approx. 26W
	Standby:	< 1W
<b>MTBF:</b>		min. 30.000 h

## Technical data

<b>Signals</b>	Image sources:	DVI, VGA
	Keyboard/Mouse:	PS/2, USB
<b>Display</b>	Height:	17"
	Technology:	LCD-TFT active Matrix
	Resolution:	1280 × 1024 (SXGA)
	Refresh rate:	60 Hz
	Pixel pitch:	0.264 mm
	Colours:	16.7 M
	Brightness:	350 nits
	Contrast ratio:	1000 (typ.)
	Horizontal angle:	+ 85 °/- 85 °
	Vertical angle:	+ 80 °/- 80 °
	Backlight:	LED
	Response time:	5 ms
<b>Casing</b>	Dimensions:	483 × 44 × 535 mm (w × h × d) w/o telescopic rails
	Installation depth:	560 - 850 mm (distance between 19" profiles)
	Weight:	Approx. 12 kg
	Cable routing:	Cable chain
<b>Power supply</b>	Supply voltage:	100-240 V AC, 50/60 Hz
<b>Power consumption</b>	Operation:	Max. 15.6 W
	Standby:	Max. 1W